











No.	케이블사진	제품사진	센서	출력	해상도	저조도	방수	전력소비	분별율	시각
1			1/4 <b>PC1030</b> 彩色CMOS	NTSC/PAL	420/480 TV Lines	1Lux/0.6Lux/ F1.2	IP66/68	max 120MA	NTSC : 580*540,PAL:580*492/ NTSC : 728*582,PAL:728*512	170°
2			1/4 <b>PC1030</b> 彩色CMOS	NTSC/PAL	420/480 TV Lines	1Lux/0.6Lux/ F1.2	IP66/68	max 120MA	NTSC : 580*540,PAL:580*492/ NTSC : 728*582,PAL:728*512	170°
3			CMOS <b>PC1030</b>	NTSC/PAL	420TV Lines	1Lux/0.6Lux/ F1.2	IP66/68	最大120MA	NTSC : 580*540,PAL:580*492	广角170°水 平105°
4			1/4 <b>PC1089</b> 彩色CMOS	NTSC/PAL	420/480 TV Lines	1Lux/0.6Lux/ F1.2	IP66/68	max 120MA	NTSC : 580*540,PAL:580*492/ NTSC : 728*582,PAL:728*512	170°
5			1/4 <b>PC1089</b> 彩色CMOS	NTSC/PAL	420/480 TV Lines	1Lux/0.6Lux/ F1.2	IP66/68	max 120MA	NTSC : 580*540,PAL:580*492/ NTSC : 728*582,PAL:728*512	170°

\* 연장 Cable류



작업온도	저장온도
- 20℃~70℃ RH95% Max	- 40℃~80℃ RH95% Max
- 20℃~70℃ RH95% Max	- 40℃~80℃ RH95% Max
- 20℃~70℃ RH95% Max	- 40℃~80℃ RH95% Max
- 20℃~70℃ RH95% Max	- 40℃~80℃ RH95% Max
- 20℃~70℃ RH95% Max	- 40℃~80℃ RH95% Max